



T1250 Series TCXO

10 MHz to 50 MHz

(Rev A)

GREENRAY INDUSTRIES, INC.

PRECISION QUARTZ TECHNOLOGY

Dual Compensated

SPECIFICATIONS

Frequency	10.0 MHz to 50.0 MHz		
Output	"C" option - CMOS Squarewave; "S" option - Clipped Sinewave		
Load	CMOS - 15pF; Clipped Sinewave – 10pf / 10kohms		
Symmetry	50% ± 10% (CMOS version)		
Temp Stability	Temp Range	Tolerance	Option
	-40 to +85°C	±3x10 ⁻⁸	T38
	-40 to +85°C	±5x10 ⁻⁸	T58
	-40 to +85°C	±1x10 ⁻⁷	T17
	(fmax-fmin)/2xfmin; EFC at center of range. Trim effect ≤ ±0.1ppM over 0 to Vs		
	EFC and temp. Hysteresis not included in stability spec.		
Freq vs. Supply	±1x10 ⁻⁷ for a 5% change		
Aging	±5x10 ⁻⁷ per year; <3ppM for 15 years		
Supply V	+5.0 or +3.3 VDC ± 5%		
Input Current	25mA max		
Phase Noise	Offset	dBc/Hz	
(10MHz typ)	10 Hz	-90	
	100 Hz	-120	
	1 kHz	-140	
	10 kHz	-150	
	100 kHz	-155	
Accel Sensitivity	≤2.5x10 ⁻⁹ /g (SD option); or ≤7x10 ⁻¹⁰ /g (LG option)		
Frequency Adjust	±7ppM typ; via 0 to Vsupply EFC; positive slope		
Environmental			
Storage Temp:	-55 to +95°C		
Random Vibration:	MIL-STD-202, Meth 214, Cond I-J		
Sine Vibration:	MIL-STD-202, Meth 204, Cond D		
Shock:	MIL-STD-202, Meth 213, Cond F		

Ordering Example:

T1250-T58-C-3.3-LG-10MHz
(Model-Stability-Output-InpV-GSense-Freq)

Pad Connections

- 1 - EFC
- 2 - N/C
- 3 - 0 V & Case Gnd
- 4 - Output
- 5 - N/C
- 6 - VSupply

