

CLD/CLDP SERIES: CLOCK OSCILLATOR, LVDS, +3.3 VDC or +2.5VDC

DESCRIPTION: A crystal controlled, high frequency, highly stable oscillator, adhering to Low Voltage Differential Signaling (LVDS) Standards. The output can be Tri-stated to facilitate testing or combined multiple clocks. The device is contained in a sub-miniature, very low profile, leadless ceramic SMD package with 6 gold contact pads. This miniature oscillator is ideal for today's automated assembly environments.

APPLICATIONS AND FEATURES:

- Infiniband; 10GbE; Network Processors; SOHO Routing; Switches; WAN Interfaces
- Common Frequencies: 106.25 MHz; 125 MHz; 150 MHz; 155.52 MHz; 156.25 MHz; 161.1328 MHz
- +3.3 VDC or +2.5VDC LVDS
- Frequency Range from 50.000 to 315 MHz
- No multiplication
- Miniature Ceramic SMD Package Available on Tape and Reel
- Lead Free and ROHS Compliant

■ ABSOLUTE MAXIMUM RATINGS:

PARAMETER	SYMBOL	VALUE	UNIT
Operating temperature range	Ta	-40...+85	°C
Storage temperature range	T(stg)	-55...+90	°C
Supply voltage	Vcc	-0.5...+5.0	VDC
Maximum Input Voltage	Vi	Vss-0.5...Vcc+0.5	VDC
Maximum Output Voltage	Vo	Vss-0.5...Vcc+0.5	VDC

■ ELECTRICAL PARAMETERS:

PARAMETER	SYMBOL	TEST CONDITIONS ^{*1}	VALUE	UNIT
Nominal Frequency	fo		50.000 ~ 315.00**	MHz
Supply Voltage	Vcc		+3.3 or +2.5 ±5%	VDC
Supply Current	Is		80.0 MAX	mA
Output Logic Type			LVDS	
Load		Connected between Out and Complementary Out	100	Ω
Output Levels	Voh	Output logic high	1.43 Typ, 1.6 Max	VDC
	Vol	Output logic low	0.9 Min, 1.10 Typ	VDC
	Vod	Differential output	247 Min, 330 Typ, 454 Max	mV
		Differential output error	50 Max	mV
	VOS	Offset Voltage	1.125 Min, 1.25 Typ, 1.375 Max	VDC
OS	Offset error	50 Max	mV	
Duty Cycle	DC	Measured at 50% of Vcc	40/60 to 60/40 or 45/55 to 55/45	%
Rise / Fall Time	tr / tf	Measured at 20/80% and 80/20% Vcc Levels	0.6 TYP ^{*2}	ns
Jitter	J	Integrated Phase tji RMS, Fj = 12 kHz...20 MHz	0.3 TYP**	ps
		Integrated Phase RMS tii offset frequency 50KHz to 80MHz	0.5 TYP**	ps
		Deterministic period Jitter tdj using wavecrest analyz.	0.0TYP **	ps
		Random period Jitter trj using wavecrest analyz.	2.5 TYP **	ps
		Peak to Peak Jitter Tp-p using wavecrest analyz.	25 TYP**	ps
Phase Noise typ. @155.52MHz	£(Δf)	Δf=10 Hz	-65	dBc/Hz
	£(Δf)	Δf=1 KHz	-120	dBc/Hz
	£(Δf)	Δf=10 KHz	-140	dBc/Hz
	£(Δf)	Δf ≥100 KHz	-145	dBc/Hz
Overall Frequency Stability	Δf/fc	Op. Temp., Aging, Load, Supply and Cal. Variations	±20, ±25, ±50, or ±100 MAX ^{*3}	Ppm
Pin 1 Output Enabled Output Disabled	En	High Voltage or No Connect	0.7•Vcc MIN	VDC
	Dis	Ground	0.3•Vcc MAX	VDC

*1 Test Conditions Unless Stated Otherwise: Nominal Vcc, Nominal Load, +25 ±3°C

*2 Frequency Dependent

*3 Not All Stabilities Available With All Temperature Ranges—Please Consult Factory For Availability

■ **PART NUMBERING SYSTEM:**

SERIES	SYMMETRY	TEMPERATURE RANGE (°C)	FREQUENCY STABILITY (Overall)	FREQUENCY (MHz)
CLD: +3.3Vdc Clock with LVDS Comp. Output CLDP: +2.5Vdc Clock with LVDS Comp. Output	A: 40/60 to 60/40% T: 45/55 to 55/45%	R: 0...+50 S: 0...+70 U: -20...+70 V: -40...+85**	K: ±20 ppm** L: ±25 ppm** H: ±50 ppm J: ±100 ppm	50.000...315.000

EXAMPLE: CLDASH-155.520

Clock Oscillator, 7x5mm Package, +3.3 VDC Supply Voltage, LVDS Output, Standard Symmetry, 0...+70°C Operating Temperature Range, ±50 ppm Total Frequency Stability, 155.520 MHz

**Above 300MHz extended temp range and ±25ppm stability may not be available, jitter may vary upon spec requirements. Please consult the factory for any custom requirements.

■ **MECHANICAL PARAMETERS:**

OUTLINE TOLERANCE:
±0.006" / 0.15mm
(Unless otherwise specified)

PIN FUNCTIONS:
[1] ENABLE/ DISABLE
[2] NO CONNECT
[3] CASE GROUND
[4] OUTPUT
[5] COMP. OUTPUT
[6] SUPPLY VOLTAGE

MARKING:
CLDASH
155.52
RAL D/C

***0.01µF external by-pass filter is recommended as seen on solder pattern.**

SOLDER PATTERN